



LTS204H Single Drum Roller

Road Roller Main Features:

1. Full hydraulic drive, reliable performance, safety.
2. CVT (continuously variable transmission), it is very easy to change the travel speed freely.
3. Hydraulic vibration, with powerful centrifugal force and excellent compaction density.
4. Hydraulic articulated steering, flexible outstanding performance.
5. High operation efficiency with best economic performance.
6. Equipped with large-size hood as engine cover, more convenient for maintenance and repair.
7. Can be adopted in variable conditions, such like compaction on the asphalt pavement and compaction on the sugared and filling materials.
8. Tread-pattern driving tires as option.

Technical specifications:

MODEL		LTS204H
Overall dimension	mm	3935X1500X25156
Operating mass	Kg	4000

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.: +86-519-68687280, 68687290

www.worldequipment.com.cn

<http://www.chinaloaders.com>

Fax. +86-519-68687282

Email sales@worldequipment.com.cn,
worldequipment@hotmail.com

Travel speed	Km/h	0-6.3
Engine model		ZN390Q
Rated power	KW	25
Rated speed	r/min	2600
Ground clearance	mm	260
Grade ability	%	25
Turning angle	.	30
Vibration amplitude	mm	0.4
Vibration frequency	Hz	45
Centrifugal force	kN	40
Vibration round width	mm	1350
Wheelbase	mm	1820
Turning radius	mm	4000
Water tank capacity	L	160

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.: +86-519-68687280, 68687290

www.worldequipment.com.cn

<http://www.chinaloaders.com>

Fax. +86-519-68687282

Email sales@worldequipment.com.cn,
worldequipment@hotmail.com