

W136 wheel loader



Komatsu technology is introduced into W136 wheel loader. The reliability and productivity of the machine is high; WEICHAI Deutz, YUCHAI or WEICHAI HUAFENG engine make the machine powerful and reliable; Torque converter and counter-shaft transmission gearbox-Komatsu technology are used. They can be assembled separately. The machine has the features of higher reliability and easier maintenance; W136 wheel loader adopts Driving Axle-Meritor technology; W136 wheel loader can be operated easily due to fully hydraulic steering system and power shift transmission; the bucket can be leveled automatically. We have many optimized working device, which can ensure higher productivity; the operation environment is comfortable because new design cabin, grammar seat and air-conditioner are employed at option. There are various working devices that are available, such as log clamp, pipe clamp, grass fork, plow, ore bucket, loose bucket, fork, etc. Therefore, this wheel loader can meet your different needs.

Specifications		
1	Bucket capacity	1.7m ³
2	Rated load	3000kg

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.: +86-519-68687280, 68687290

www.worldequipment.com.cn

<http://www.chinaloaders.com>

Fax. +86-519-68687282

Email sales@worldequipment.com.cn,
worldequipment@hotmail.com



WORLD EQUIPMENT (CHANG ZHOU) CO., LTD

3	Transportation dimension (L×W×H)	7500×2430×3120mm
4	Wheelbase	2760mm
5	Thread	1800mm
6	Max. breakout force	138KN
7	Max. dumping height	3020/3250mm
8	Dump distance	1200mm
9	Total time	11s
10	Operating weight	9500kg
Engine		
1	Model	Cummins engine 6BT5.9-C125
2	Pattern	Turbocharger, Inline, water-cooled, 4-stroke, direct injection
3	Rated power/speed	92kw/2200rpm
4	Max. torque	860N.m
5	Normal fuel consumption	162g/kW.h
6	Total displacement	6L
7	Fuel	0#or-10 # 0 # or-10 # light diesel
Torque converter and transmission system		
1	Model of torque converter	YJ320B-1
2	Pattern	3-element single stage
3	Transmission type	Full-power shift, counter shift type
4	Number of gear	4 forward, 2 reverse
5	Max. travel speed	40km/h
Alex		
1	Alex	Xuzhou/laiyang
2	Main reducer pattern	Arc taper gear, moderation of first grade
3	Pattern of wheel side moderation	single stage planetary
Tire		
1	Tire Size	17.5-25
Steering system		
1	Pattern	Articulated and hydraulic steering

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.: +86-519-68687280, 68687290

www.worldequipment.com.cn

<http://www.chinaloaders.com>

Fax. +86-519-68687282

Email sales@worldequipment.com.cn,

worldequipment@hotmail.com



WORLD EQUIPMENT (CHANG ZHOU) CO., LTD

2	Min. turning radius(outside of bucket)	5700mm
3	Max. turning angle	37°±1
Hydraulic system		
1	Implement pump	CBGV2100
2	Displacement	100ml/r
3	System working pressure	27.5MPa
4	Distribution device model	DF25.2C
Brake system		
1	Service brake	Air assisted oil disc on four wheel
2	Parking brake	flexible shaft control, outside bunch drum type

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.: +86-519-68687280, 68687290

www.worldequipment.com.cn

<http://www.chinaloaders.com>

Fax. +86-519-68687282

Email sales@worldequipment.com.cn,
worldequipment@hotmail.com