

W156 Wheel Loader

- 1. This W156 wheel loader features high-quality engine, low oil consumption, low noises, and reliable performance.
- 2. It has been designed with double-turbo hydraulic torque converter, and high-efficient planet-power shifting transmission.
- 3. Developed on the basis of advanced European technology, its fortified axles have stronger loading capacity, large driving force, and more reliable and stable performance.
- 4. Its integral instrument platform is of reliable quality, durability, long service lifespan, and elegant appearance.
- 5. Its rear frame is fitted with box structure, and hinged panels with low stress and high strength steel.
- 6. Most of the components W156 wheel loader, like cylinders, pumps, valves, are from international famous brands, which ensure the stability and reliability of this loader.

Main Specification

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang

Su, China

Tel.:+86-519-68687280, 68687290 **Fax**. +86-519-68687282

www.worldequipment.com.cn http://www.chinaloaders.com

	Bucket	V156 Wheel Loader		
1	Capacity	3.0M³		
2	Rated Load	5000kg		
3	Travelling Speed			
		Forward 1st	0-11.5km/h	
		Forward 2nd	0-37.5km/h	
		Reverse 1st	0-17km/h	
4	Max. Traction	165±5kN		
5	Max.Break Out Force	150±5kN		
6	Min. Turning Radius (outside tires)	6700±50mm		
7	Max. Dumping Height	2970±50mm		
8	Max. Dumping Reach	1200±50mm		
9	Total Hydraulic Cycle Time	≤11.1s		
10	Full Bucket Lifting Time	≤5.76s		
11 Wheel	Base	3427±30mm		
12 T	read Width	2300±10mm		
13 D	imensions (L×W×H)	L:8075×W:2960×H:3500mm		
14	Min. Clearance Over Ground	380±20mm		
15 O	perating Weight	16200±200kg		
Diesel Engine				

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang Su, China

Tel.:+86-519-68687280, 68687290

www.worldequipment.com.cn http://www.chinaloaders.com **Fax**. +86-519-68687282

WORLD World Equipment (Changzhou) CO., Ltd.

EGOTTMEN	- P			
1	Diesel Engine Model ofW156 Wheel Loader	WEICHAI WD615 WD615	CATERPILLAR C6121 C6121	CUMMINS6CTA8.3-C21 666CTA8.3-C215
2	Туре	Direct injection, turbocharged, water cooling, 4 strokes, 6 cylinders		
3	Rated Output	162kW	162kW	160kW
4	Rated Speed	2200rpm		
5	Max. Torque	855N.m	860N.m	908N.m
Transmission				
1	Model	ZL50 Hangzhou Advance Gearbox Group Co., Ltd		
2	Rated Input Speed	2200rpm		
3	Transmission Type	two forward and one reverse gears/power shift, planet type		
Mechanical Gear Ratios				
1	Gear I	2.4346		
2	Gear II	0.6532		
3	Reverse	1.7814		
4	Hydraulic Oil Pressure	1.10-1.40Mpa		
5	Inlet Oil Pressure OfTorque Convertor	0.30-0.45Mpa		
6	Outlet Oil Pressure Of Torque Convertor	0.20-0.30Mpa		
7	Lubricating Oil Pressure	0.10-0.20Mpa		
8	Max. Permissible Temp &	120℃		

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang

Su, China

Tel.:+86-519-68687280, 68687290 **Fax**.

www.worldequipment.com.cn http://www.chinaloaders.com **Fax**. +86-519-68687282

WORLD World Equipment (Changzhou) CO., Ltd. Outlet Of Torque Convertor

Address: Room 513, NO.368 Han Jiang Road, Jin Cheng Plaza, Chang Zhou, Jiang

Su, China

Tel.:+86-519-68687280, 68687290 www.worldequipment.com.cn

www.worldequipment.com.cn http://www.chinaloaders.com **Fax**. +86-519-68687282